


SPECIFICATIONS



MODEL SPECS	A	B	C	D	E	F	G
HBAE 3030-35C (mm)	5800	2965	1840	760	760	812	760
(in)	228	116	72	30	30	32	30
HBAE 3630-50C (mm)	5985	2965	1840	914	760	1000	760
(in)	235	116	72	36	30	40	30
HBAE 3040-50C (mm)	5985	3490	1840	760	1016	1000	1016
(in)	235	137	72	30	40	40	40

MODEL	HBAE 3030-35C	HBAE 3630-50C	HBAE 3040-60C
Expanded Bale Size			
High (mm / in)	760 / 30	914 / 36	760 / 30
Wide (mm / in)	760 / 30	760 / 30	1016 / 40
Long (mm / in)	1200 / 47	1200 / 47	1200 / 47
Bale Weight			
Printers Trim (kg)	250 - 320	275 - 375	300 - 420
(lbs)	562 - 720	618 - 843	675 - 945
Operating Pressure (Tons)	35	50	60
Machine Capacity (Tonnes) Based / Hr. on Printers Trim	1.3	2.5	3.2
Ram Face Pressure	87	93	112
Cycle Time (No Load)	20	15	15
Electric Motor (kW)	15	22	22
Main Cylinder (mm) (in)	177 7	203 8	203 8
Tension Cylinder (mm) (in)	127 5	127 5	127 5
Bale Tie Wires	3	3	3
Shipping Weight Approx. (kg)	8500	8900	9350

Performance rates, bale weights and bale densities are subject to moisture content, material pre-bale density, method of feeding and other variables in baling.



proudly manufactured by:



246 Grand Junction Road
 Athol Park S.A. 5012
Ph: +61 8 8341 0177
 Fax: +61 8 8341 1955

Visit our website
www.torqind.com

email: sales@torqind.com

Call Toll Free in Australia
 (excluding South Australia)

1800 064 455